

S5-GR1P(2.5-6)K

Solis Single Phase Inverters



360 degree

Features:

- ▶ Max. efficiency 98.1%
- ▶ Super high frequency switching technology
- ▶ Wide voltage range and low startup voltage
- ▶ 2 MPPT design with precise MPPT algorithm
- ▶ Intergrated Export Power Manager (EPM)
- ▶ Integrated AFCI (DC arc-fault circuit protection)
- ▶ Maximum string input current 12.5A
- ▶ Compact and lightweight
- ▶ Friendly and adaptable connection to the grid



Model:

S5-GR1P2.5K	S5-GR1P3K	S5-GR1P3.6K
S5-GR1P4K	S5-GR1P4.6K	S5-GR1P5K
S5-GR1P6K		

Datasheet

Model Name	S5-GR1P2.5K	S5-GR1P3K	S5-GR1P3.6K	S5-GR1P4K	S5-GR1P4.6K	S5-GR1P5K	S5-GR1P6K
------------	-------------	-----------	-------------	-----------	-------------	-----------	-----------

Input DC

Recommended max. PV power	3 kW	3.5 kW	4.2 kW	4.6 kW	5.3 kW	5.8 kW	6.6 kW
Max. input voltage	550 V	600 V					
Rated voltage	250 V	330 V					
Start-up voltage	60 V	120 V					
MPPT voltage range	50-450 V	90-520 V					
Max. input current	12.5 A / 12.5 A						
Max. short circuit current	17.2 A / 17.2 A						
MPPT number/Max. input strings number	2/2						

Output AC

Rated output power	2.5 kW	3 kW	3.6 kW	4 kW	4.6 kW	5 kW	6 kW
Max. apparent output power	2.8 kVA	3.3 kVA	4 kVA	4.4 kVA	5 kVA	5 kVA	6 kVA
Max. output power	2.8 kW	3.3 kW	4 kW	4.4 kW	5 kW	5 kW	6 kW
Rated grid voltage	1/N/PE, 220 V / 230 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	11.4 A / 10.9 A	13.6 A / 13.0 A	16.0 A / 15.7 A	18.2 A / 17.4 A	20.9 A / 20.0 A	22.7 A / 21.7 A	27.3 A
Max. output current	13.3 A	15.7 A	16.0 A	21.0 A	23.8 A	25.0 A	27.3 A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)						
THDi	<3%						

Efficiency

Max. efficiency		97.8%				98.1%	
EU efficiency		97.1%				97.3%	

Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	Yes
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Integrated AFCI (DC arc-fault circuit protection)	Yes*
Integrated DC switch	Optional

General Data

Dimensions (W*H*D)	310*543*160 mm
Weight	11.5 kg
Topology	Transformerless
Self consumption (night)	<1 W
Operating ambient temperature range	-25 ~ +60°C
Relative humidity	0-100%
Ingress protection	IP65
Cooling concept	Natural convection
Max. operation altitude	4000 m
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-3

Features

DC connection	MC4 connector
AC connection	Quick connection plug
Display	LCD
Communication	RS485, Optional: Wi-Fi, GPRS

* Activation required.